

The 1120-F MiniButt fiber optic splice closure is designed for low count fiber splicing. The closure incorporates an integrated gasket to prevent the ingress of water but to allow for ease in access.



### Applications

- Hand holds
- Man holes
- Aerial
- Wall/Pole mount

### Features

- Supports both Inline or Butt configurations
- Up to 24 single fusion or 192 mass fused fibers
- Compact size
- Up to four cable entries with OD range of 0.3 to 0.63"
- Above or below ground installations
- Constructed with impact and corrosion resistant materials
- Integrated "F" pressure testing valve and grounding lugs
- RUS listed
- Made in USA



### Specifications

Property	Value
Cable Entry Points	4 (OD 0.3 – 0.63")
Splice Trays	2
Dimensions	15"L x 6.5"W x 3"D
Packaging	
Weight	7 lbs

### Ordering Information

Model #	Description
1120-F	SPLICE CASE MINIBUTT EMPTY, CAPACITY 4 CABLES 2 SPLICE TRAYS
TRAY1120	SPLICE TRAY 7 INCH 12 FIBER SINGLE FUSION /96 MASS

### Accessories

1100-A	1100-T	1100-SS	1100-W
VERTICAL AERIAL HANGER BRACKET	HORIZONTAL AERIAL HANGER BRACKET	ADSS MOUNTING KIT	WALL/POLE MOUNTING BRACKETS
			