

The TSL-5 Fiber Termination Panel provides connectivity up to 48 or 96 (high density). The 3RU shelf accepts 8 adapter panels or modules and offers integrated fiber splicing. TSL shelves have been designed to meet Telcordia GR-63 and GR-449 Fiber Distribution Frame System requirements.

Applications

- Telecommunications closets
- Central offices
- Data centers
- Remote distribution terminals

Features

- Available loaded with adapters, pigtails and splice trays
- Integrated splice tray mounting bracket
- 19 or 23 inch rackmount
- LGX adapter plate compatible
- Slide out master tray
- Removable top cover and rear door for easy splice access
- Left or right cable entry, 1 strain relief kit included

Specifications

Property	Value
Adapter Plates	8
Splice Trays	4
Dimensions	3RU 5.25" H x 17.0" W x 11.0" D
Packaging	8.0"H x 20.0" W x 14.0" D
Weight	15 lbs empty, 17 lbs typical loaded
Material	Aluminum, Central Office White

Ordering Information

Model #	Description
RM3UWS	TSL-5 3RU PATCH PANEL EMPTY 8 PLATE, 4 SPLICE TRAY CAPACITY
TRAY7	SPLICE TRAY 7 INCH 12 FIBER SINGLE FUSION
TRAY8	SPLICE TRAY 8-3/4 INCH 24 FIBER SINGLE FUSION
LG1-xxxxxx-W	LG1 SERIES ADAPTER PLATES IN WHITE (SEE LG1 PRODUCT GUIDE)

Factory Loading Options:

R M 3 U W S

