

The TSL-9 Fiber Termination Panel provides connectivity up to 144 Ports (288 ports LC only). The 5RU shelf accepts 12 LGX 170 long adapter plates and offers integrated mass ribbon fiber splicing module. 900um pigtailed and splicing is available with the optional 3RU SPS-5 splice bay installed. TSL shelves have been designed to meet Telcordia GR-63 and GR-449 Fiber Distribution Frame System requirements.

### Applications

- Telecommunications closets
- Central offices
- Data centers
- Remote distribution terminals

### Features

- Available with adapters, and ribbon pigtailed or a preterminated fiber stub
- Integrated Ribbon splice module
- 19 or 23 inch rackmount & wallmount
- LGX 170 adapter plate compatible
- Patch or patch and splice



### Specifications

Property	TSL-9	TSL-9/SPS-5
Adapter Plates	12	12
Splice Trays	0 (integrated mass splice chip)	6
Dimensions	5RU 8.75" H x 17.0" W x 11.0" D	8RU 14.0" H x 17.0" W x 11.0" D
Packaging	12.0"H x 20.0" W x 14.0" D	18.0" H x 20.0" W x 14.5" D
Weight	13 lbs empty, 15 lbs typical loaded	23 lbs empty, 26 lbs typical loaded
Material	Aluminum, Central Office White	

### Ordering Information

Model #	Description
RM5UWS	TSL-9 5RU PATCH PANEL EMPTY 12 LGX-170 PLATE CAPACITY
RM3UWSS	SPS-5 3RU SPLICE BAY 6 SPLICE TRAY CAPACITY
TRAY8	SPLICE TRAY 8-3/4 INCH 24 FIBER SINGLE FUSION
LG7-xxxxxx-W	LG7 SERIES ADAPTER PLATES IN WHITE (SEE LG7 PRODUCT GUIDE)

### Factory Loading Options:

